

HY-G1/144 HY-G1/144H MONOCRYSTALLINE MODULE 390-410W

410W

Maximum Power Output

20.4%

Maximum Module Efficiency

0~+5W

Power Output Guarantee



Ideal choice for large scale ground installation



Sand blowing test, salt mist test and ammonia test passed to endure harsh environments



Selected encapsulating material and stringent production process control ensure the product is highly PID resistant and snail trails free




Optimized system performance due to module level current sorting



Special cutting and soldering technology leads to low hot spot risk



Highly transparent self-cleaning glass brings additional yield and easy maintenance



Cell Type


9BB(158.75mm)



Delivers Reliable Performance Over Time

- Manufacturer of crystalline silicon photovoltaic modules
- Fully automatic facility and world-class technology
- Rigorous quality control to meet the highest standard: ISO9001:2015, ISO14001: 2015 and OHSAS: 18001 2007
- Tested for harsh environments (salt mist, ammonia corrosion and sand blowing test: IEC 61701, IEC 62716, DIN EN 60068 -2- 68)
- Long term reliability tests
- 2x100% EL inspection ensuring defect-free modules

LINEAR PERFORMANCE WARRANTY



10 Years Product Warranty 25 Years Linear Power Warranty

* Please refer to standard warranty for details

Product certification



**EXCELLENCE
BY DESIGN™**

TECHNICAL SPECIFICATIONS

Electrical Specification (STC*)

Maximum Power	Pmax[W]	390	395	400	405	410
Maximum Power Voltage	Vmp[V]	39.92	40.27	40.61	40.96	41.29
Maximum Power Current	Imp[A]	9.77	9.81	9.85	9.89	9.93
Open Circuit Voltage	Voc[V]	48.33	48.63	48.93	49.23	49.53
Short Circuit Current	Isc[A]	10.29	10.33	10.36	10.39	10.43
Module Efficiency	[%]	19.4	19.7	19.9	20.1	20.4
Power Output Tolerance	[W]			0~+5		

* Irradiance 1000W/m², Module Temperature 25°C, Air Mass 1.5

Electrical Specification [NOCT*]

Maximum Power	Pmax [W]	291.65	295.13	298.24	301.37	304.90
Maximum Power Voltage	Vmp[V]	37.20	37.50	37.80	38.10	38.40
Maximum Power Current	Imp [A]	7.84	7.87	7.89	7.91	7.94
Open Circuit Voltage	Voc [V]	45.00	45.30	45.60	45.80	46.10
Short Circuit Current	Isc [A]	8.32	8.35	8.38	8.40	8.43
Irradiance 800W/m ² , Ambient Temperature 20°C, Wind Speed 1m/s						

Mechanical Data

Number of Cells	144 Cells (6x 24)
Dimensions of Module L'W'H (mm)	2008x1002x35mm (79.05x39.44x1.38 inches)
Weight (kg)	22.5 kg
Glass	High transparency solar glass 3.2mm (0.13 inches)
Backsheet	White
Frame	Silver, anodized aluminium alloy
J-Box	IP68 Rated
Cable	4.0mm ² (0.006 inches ²),300mm (11.8 inches)
Number of diodes	3
Wind/ Snow Load	2400Pa/ 5400Pa*
Connector	MC Compatible

*For more details please check the installation manual

Temperature Ratings

Nominal Operating Cell Temperature [NOCT]	44±2°C
Temperature Coefficient of Isc	+0.06%/°C
Temperature Coefficient of Voc	-0.30%/°C
Temperature Coefficient of PMAX	-0.39%/°C

Maximum Ratings

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC-[H]
Max Series Fuse Rating	20A


Packaging Configuration

Module per box	30 pieces
Module per 40' container	660 pieces


Optional

Connector	■ MC Original
-----------	---------------


Module Dimension




Back View



I-V Curve at Different Temperature (410W)



I-V/P-V Curve at Different Irradiation (410W)



MONOCRYSTALLINE390-410W07072020 Excellence by Design® is a registered trade mark of Heliodyne Inc.

Heliodyne Hong Kong Ltd • Room 2407,24/F,Windsor House,311 Gloucester Road • Cause Bay,Hong Kong
 • Information and Support: sales@heliodynehongkong.com
 • www.heliodynehongkong.com